Specifications







Eaton DT364URK

Eaton Heavy duty double-throw non-fused safety switch, 200 A, NEMA 3R, Painted galvanized steel, Non-fusible, Three-pole, Three-wire, 600 Vac, 250 Vdc

General specifications	
PRODUCT NAME	Eaton heavy duty double-throw non-fused safety switch
CATALOG NUMBER	DT364URK
UPC	782113613987
PRODUCT LENGTH/DEPTH	11.26 in
PRODUCT HEIGHT	37.69 in
PRODUCT WIDTH	19.15 in
PRODUCT WEIGHT	80 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed
CATALOG NOTES	Suitable for service entrance use with a neutral or ground lug kit installed
GLOBAL CATALOG	DT364URK
PRODUCT TYPE	Double-throw non-fused safety switch

Powering Business Worldwide

Product specifications

TYPE	Heavy Duty, Double-Throw
AMPERAGE RATING	200A
NUMBER OF POLES	Three-pole
VOLTAGE RATING	600 Vac, 250 Vdc
ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Non-fusible
NUMBER OF WIRES	3

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
MULTIMEDIA	Switching Devices Flex Center ARMS Enclosed Circuit Breaker Double Up on Safety
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DT364URK
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.