Product specifications

Eaton C22G10

Catalog Number: C22G10

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 10 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C22G10

UPC
051712667326

EAN
5027590495189

Product Length/Depth
58 mm

Product Height
22.2 mm

Product Width
22.2 mm

Product Weight
53.9 g

Warranty
1 year limited

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269

Powering Business Worldwide

Product specifications

Fuse indicator
Other

Construction size
22 mm x 58 mm

Rated voltage AC
690 V

Connection
Ferrule end x ferrule end

Quantity
10

Current type
AC

Suitable for
CH22 Modular fuse holder

Material
Ceramic

Mounting method
22 x 58 mm CH Modular fuse holder

Release characteristic
Other

Amperage Rating
10 A

Frequency rating - max
62 Hz

Utilization category
gG (cable protection/equipment protection)

Watt losses
1.5 W

Fuse type
C22G

Type
fuse

Fuse shape
Cylindrical

Resources

Catalogs
Bussmann series complete full line catalog no. 1007

Compliance information
CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets
720115 Cylindrical fuses

Breaking capacity

80 kA

Fuse size

22 x 58 mm

Frequency rating - min

45 Hz

Class

Class C gL/gG

Voltage rating

690 V

Application

for industrial applications

for general purpose use

Voltage type

AC

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia