# Specifications



Photo is representative





## Eaton BA43A

NEMA A200 Thermal Overload Relay, Three-pole, Starter mounted, NEMA , Thermal Type B, Class 20, 1NC Auxiliary Contact, Ambient Compensated , Full load range 19-135A

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Freedom NEMA overload relay |
| **CATALOG NUMBER** | BA43A |
| **UPC** | 786678003238 |
| **PRODUCT LENGTH/DEPTH** | 8.2 in |
| **PRODUCT HEIGHT** | 5.1 in |
| **PRODUCT WIDTH** | 6 in |
| **PRODUCT WEIGHT** | 2.1 lb |
| **WARRANTY** | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| **CERTIFICATIONS** | UL Listed<br>CSA Certified |
| **CATALOG NOTES** | Replacement for Type A Overload Relays in Manual Reset Mode (3-Pole Only). Includes contactor mounting bracket, overload relay and connection straps to contactor. |
| **PRODUCT TYPE** | Overload relay |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **MODIFICATION** | 1NC Auxiliary Contact, Ambient Compensated |
| **DESIGN** | NEMA |
| **FULL LOAD CURRENT RANGE** | 19-135A |
| **MOUNTING** | Starter |
| **NUMBER OF POLES** | Three-pole |
| **SPECIAL FEATURES** | Heaters required |
| **TRIP TYPE** | Thermal Type B, Class 20 |
| **TYPE** | A200 |

## Resources

| | |
|---|---|
| CATALOGS | Motor Control and Protection, NEMA Contactors and Starters, Volume 5, Tab 2 |
| INSTALLATION INSTRUCTIONS | Instructions for A200, A210, A250 size 6, two- or three-pole non-reversing or reversing motor controllers |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - BA43A |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.