Product specifications

Eaton V48M28T15EES6

Catalog Number: V48M28T15EES6

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 150°C rise w/ 200°C insulation systeam, 15 kVA, EE, S6



Photo is representative

General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
V48M28T15EES6

UPC
786680113505

Product Length/Depth
16.5 in

Product Height
30 in

Product Width
23 in

Product Weight
209 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL Listed

Catalog Notes
Grade 316 stainless steel enclosure (does not imply NEMA 4X rating) NEMA TP-1 efficient.

Powering Business Worldwide

Physical Attributes

Coil material
Aluminum

Frame
912D

Tap size
2 at +2.5% FCAN 4 at -2.5% FCBN

Type
Dry type distribution ventilated transformer

Wiring connection
280B

Performance Ratings

Frequency rating
60 Hz

Primary voltage
480 V

Secondary Voltage
208 Y/120 V

Temperature rise
150 °C rise

Volt ampere rating
15 kVA

Miscellaneous

Weathershield
WS38S

Resources

Catalogs
Eaton's Volume 2—Commercial Distribution

Specifications and datasheets
Eaton Specification Sheet - V48M28T15EES6

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia