Product specifications

Eaton FWP-80G22F



Catalog Number: FWP-80G22F

Eaton Bussmann series FWP high speed fuse, 690V, 80A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name
Eaton Bussmann series high speed cylindrical fuse

Catalog Number
FWP-80G22F

UPC
051712689724

EAN
5027590501156

Product Length/Depth
58 mm

Product Height
22 mm

Product Width
22 mm

Product Weight
52 g

Warranty
No warranty

Compliances
CE Marked
RoHS Compliant

Certifications
UL Recognized
IEC Rated

Powering Business Worldwide

Product specifications

Fuse indicator
Other

Interrupt rating
200 kAIC

Construction size
22 mm x 58 mm

Clearing (I2T)
5448

Connection
Ferrule end x ferrule end

Material
Ceramic

Release characteristic
Other

Amperage Rating
80 A

Frequency rating - max
62 Hz

Utilization category
gR (general purpose semiconductor protection)

Watt losses
14 W

Fuse type
FWP-G22F

Accessories
CH22 Modular fuse holder

Type
High speed fuse

Fuse shape
Cylindrical

Breaking capacity
200 kA

Fuse size
22 x 58 mm

Frequency rating - min

Resources

Catalogs
IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information
CE High-speed, cylindrical gR fuse-links

UKCA High-speed, cylindrical gR fuse-links

Technical data sheets
10469 22 x 58 mm gR cylindrical fuse links

45 Hz

Class

Class gR

Pre arc (I2T)

1092

Voltage rating

690 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC

Packaging type

Standard

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia