Specifications







Eaton E57SAL18A2E

Inductive Proximity Sensor, E57, Straight, Unshielded, 360° viewable LED, 6.6 ft, 250 mA at 40-240 Vac/20-250 Vdc, <3%, PVC, 2-wire AC/DC, NO, 40-250 Vac 50/60 Hz, 20-250 Vdc

General specifications	
PRODUCT NAME	Eaton E57 inductive proximity sensor
CATALOG NUMBER	E57SAL18A2E
UPC	782113381930
PRODUCT LENGTH/DEPTH	2.54 in
PRODUCT HEIGHT	0.71 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.7 lb
WARRANTY	1 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Listed CSA Certified

Powering Business Worldwide

Product specifications

TYPE	E57
CONTACT RATING	250 mA at 40-240 Vac/20-250 Vdc
ACTUATOR FUNCTION	Unshielded
CABLE TYPE	Polyvinyl Chloride (PVC)
ACCURACY	< 3%
ENCLOSURE MATERIAL	303 stainless steel
CONTACT CONFIGURATION	2-wire AC/DC, NO
SERIES	E57
ENVIRONMENTAL RATING	NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K
TEMPERATURE RATING	-13 to 158 °F
CORD LENGTH	79.2 ft
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-13 °F
MAXIMUM AC CURRENT	250 mA
MAXIMUM DC CURRENT	250 mA
INPUT VOLTAGE	40-250 Vac at 50/60 Hz, 20-250 Vdc
LED INDICATOR	360 ° viewable LED
PROTECTION	Resettable short circuit, overload

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications Sensing Solutions, Inductive Proximity Sensors, Volume 8, Tab 3
MULTIMEDIA	We make what matters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - E57SAL18A2E

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.