Specifications



Photo is representative

Eaton A25SNE40A

Eaton definite purpose starter, 40 A, Coil: 110-120 V, 50/60 Hz, 20 HP at 460 V, Separate control wiring, Open with metal mounting plate, 40 A IFL, Three-phase, Box lugs (posidrive setscrew), Non-reversing

General specifications

PRODUCT NAME	Eaton definite purpose starter
CATALOG NUMBER	A25SNE40A
UPC	782113757551
PRODUCT LENGTH/DEPTH	3.66 in
PRODUCT HEIGHT	8.08 in
PRODUCT WIDTH	2.56 in
PRODUCT WEIGHT	1.8 lb
WARRANTY	1 year
CERTIFICATIONS	CSA Certified UL Recognized
PRODUCT TYPE	Definite purpose starter

Powering Business Worldwide

Product specifications

AMPERAGE RATING	40A
PHASE	Three-phase
TYPE	Non-reversing
COIL	110-120 Vac, 50/60 Hz
CONTROL CHARACTERISTICS	Separate control
ENCLOSURE	Open with metal mounting plate
INDUCTIVE FULL LOAD	40 A IFL
TERMINALS	Box lugs (posidrive setscrew)
MODEL	Starter

Resources

CATALOGS	Motor Control and Protection, Definite Purpose Contactors and Starters, Volume 5, Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - A25SNE40A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.