Specifications

Eaton XTOBP40CC1

Catalog Number: XTOBP40CC1

Eaton XT IEC bimetallic overload relay, 0.24-0.4A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 18-32A contactor, 10A trip type



General specifications

Product Name
Eaton XT IEC bimetallic overload relay

Catalog Number
XTOBP40CC1

EAN
4015082784447

Product Length/Depth
4 in

Product Height
2 in

Product Width
3.5 in

Product Weight
0.5 lb

Compliances
CE Marked
ATEX Compliant
RoHS Compliant

Certifications
UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes
Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

Powering Business Worldwide

Product specifications

Overload range

0.24-0.4 A

Type

XT IEC Bimetallic Overload Relay

Used with

18-32A contactor

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Trip type

10 A

Resources

Brochures

C440 Electronic Overload Relay

Drawings

XTOB_CC1 AutoCAD 2D Footprint

XTOB_CC1 3D Model Xchange

XTOB_CC1 3D Inventor

XTOB_CC1 2D Drawing Xchange

XTOB_CC1 AutoCAD 2D Footprint (mm)

XTOB_CC1 2D PDF

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Global Data Sheet - XTOBP40CC1

Eaton Specification Sheet - XTOBP40CC1

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia