Product specifications

Eaton FWX-3A14F



Catalog Number: FWX-3A14F

Eaton Bussmann series FWX high speed fuse, 600V, 3A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name
Eaton Bussmann series high speed cylindrical fuse

Catalog Number
FWX-3A14F

UPC
051712795159

EAN
5027590501408

Product Length/Depth
58 mm

Product Height
35 mm

Product Width
89 mm

Product Weight
21.8 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

30 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Watt losses

2.8 W

Fuse shape

Cylindrical

Interrupt rating

200 kAIC

Connection

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Technical data sheets

720006 FWX

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

690 V

Fuse type

FWX-A14F

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia