Product specifications

Eaton C25DNF340A

Catalog Number: C25DNF340A

Eaton definite purpose contactor, Quick, Class J, 600V, 60A, 40A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and 3P, 40A, Contactor, 3P, 50A, Box lugs (posidrive setscrew) and quick connect terminals , Non-reversing



General specifications

Product Name	**Catalog Number**
Eaton definite purpose contactor	C25DNF340A
UPC	**Product Length/Depth**
782116300662	3.35 in
Product Height	**Product Width**
3.75 in	2.4 in
Product Weight	**Warranty**
0.9 lb	1 year
Compliances	**Certifications**
RoHS Compliant	CSA Certified UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Amperage Rating

40A

Number Of Poles

Three-pole

Type

Non-reversing

Coil

110-120 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

40 A

Model

Contactor

Resistive load

50 A

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25DNF3 3D Model Xchange

C25DNF3 2D Drawing Xchange

C25DNF3 AutoCAD 2D Footprint

C25DNF3 2D PDF

C25DNF3 AutoCAD 2D Footprint (mm)

C25DNF3 3D Inventor

Specifications and datasheets

Eaton Specification Sheet - C25DNF340A

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia