Specifications



Eaton 13100RS9035

Eaton Comet 18mm tubular photoelectric sensor, Diffuse Reflective, 48 in range, Right Angle, Output ON, 6.6 ft, 300 mA AC/DC at 20-264 Vac/15-30 Vdc, PVC, AC: L1 switched, DC: NPN open collector, 20-264 Vac 50/60 Hz, 15-30 Vdc (NPN)

General specifications	
PRODUCT NAME	Eaton Comet 18mm tubular photoelectric sensor
CATALOG NUMBER	13100RS9035
UPC	782114629949
PRODUCT LENGTH/DEPTH	2.55 in
PRODUCT HEIGHT	0.71 in
PRODUCT WIDTH	0.47 in
PRODUCT WEIGHT	0.7 lb
WARRANTY	3 year
CERTIFICATIONS	UL Listed cUL Listed CE
PRODUCT TYPE	Tubular photoelectric sensor

Powering Business Worldwide

Product specifications

TYPE	Photoelectric Sensor
CONTACT RATING	300 mA AC/DC at 20-264 Vac/15-30 Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Polyurethane foam (RIM)
CONTACT CONFIGURATION	AC: L1 switched DC: NPN open collector
SENSOR TYPE	Diffuse reflective
INPUT VOLTAGE	20-264 Vac at 50/60 Hz, 15-30 Vdc (NPN)
LED INDICATOR	Output ON
PROTECTION	Latching short circuit
CORD LENGTH	79.2 ft
MAXIMUM AC CURRENT	300 mA
MAXIMUM DC CURRENT	300 mA
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-40 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13, IP69K

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications Sensing Solutions,Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 13100RS9035

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.