Specifications



Photo is representative

Eaton XV-102-D6-57TVRC-10

Eaton XV100 basic human machine interface (HMI), 2nd generation CE, XSoft-CoDeSys/Galileo OS, Retentive memory, USB host, RS-232 base unit, CANopen communication, RS-232, RS-485 interface, 5.7 in TFT resistive touch (VGA) display

General specifications	
PRODUCT NAME	Eaton XV100 basic human machine interface (HMI)
CATALOG NUMBER	XV-102-D6-57TVRC-10
EAN	7640130096752
PRODUCT LENGTH/DEPTH	11 in
PRODUCT HEIGHT	3 in
PRODUCT WIDTH	7.5 in
PRODUCT WEIGHT	1.73 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed cULus Listed
CATALOG NOTES	All 1xx performance class units have 400MHz processor,64 MB DRAM, 1x10/100 Ethernet, and 1x USB device.

Powering Business Worldwide

Product specifications

BASE UNIT	Retentive memory, USB host, RS-232
BEZEL	Blank front
COMMUNICATION	CANopen
SERIAL INTERFACE	RS-232, RS-485
DISPLAY	5.7 in TFT resistive touch (VGA)
OPERATING SYSTEM	XSoft-CoDeSys Galileo

Resources

MULTIMEDIA	HMI-PLC overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XV-102-D6-57TVRC-10
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.