Specifications

Photo is representative

Eaton FAZ-B32/2

Eaton FAZ supplementary protector,UL 1077 Industrial miniature circuit breaker - supplementary protector,Low levels of inrush current are expected,32 A,15 kAIC,Two-pole,3-5X /n,50-60 Hz,Standard terminals,B Curve

General specifications	
PRODUCT NAME	Eaton FAZ supplementary protector
CATALOG NUMBER	FAZ-B32/2
EAN	4015082787370
PRODUCT LENGTH/DEPTH	1.38 in
PRODUCT HEIGHT	1.38 in
PRODUCT WIDTH	1.5 in
PRODUCT WEIGHT	0.53 lb
WARRANTY	1 year
CERTIFICATIONS	UL 1077 CSA Std. C22.2 No.235 IEC 60947-2
CATALOG NOTES	For applications that require protection due to potential wiring damage at low fault conditions.
PRODUCT TYPE	Supplementary protector

Powering Business Worldwide

Physical Attributes

NUMBER OF POLES	Two-pole
TERMINALS	Standard
TYPE	UL 1077 Industrial miniature circuit breaker - supplementary protector

Performance Ratings

AMPERAGE RATING	32 A
CIRCUIT PROTECTION	B curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	15 kAIC
TRIP TYPE	T17

Miscellaneous

APPLICATION	Suitable for applications where low levels of inrush current are expected

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-B32/2

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.