Specifications







Eaton E57-18GU08-DDB

Inductive Global Proximity Sensor, E57, 8 mm range, Straight, 18 mm, Unshielded, Output ON, M12, 100 mA at 10-30 Vdc, 4 pin, <2.0% sensing range, 2-wire DC, NC, 10-30 Vdc

General specifications	
PRODUCT NAME	Eaton E57 inductive proximity sensor
CATALOG NUMBER	E57-18GU08-DDB
UPC	782114665077
PRODUCT LENGTH/DEPTH	3.15 in
PRODUCT HEIGHT	0.71 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.2 lb
WARRANTY	1 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Listed CSA Certified

Powering Business Worldwide

Product specifications

TYPE	Inductive Global Proximity Sensor
CONTACT RATING	100 mA at 10-30 Vdc
ACTUATOR FUNCTION	Unshielded
ACCURACY	< 2.0% sensing range
ENCLOSURE MATERIAL	Nickel plated brass
CONNECTION	M12
CONTACT CONFIGURATION	2-wire DC, NC
SERIES	E57
ENVIRONMENTAL RATING	IP67, IP69K
NUMBER OF PINS	4
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-13 °F
MAXIMUM DC CURRENT	100 mA
INPUT VOLTAGE	10-30 Vdc
LED INDICATOR	Output ON
PROTECTION	Short circuit

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications Sensing Solutions, Inductive Proximity Sensors, Volume 8, Tab 3
MULTIMEDIA	We make what matters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - E57-18GU08-DDB

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.