Specifications



Eaton CMBX1212P200BTS

Type CH Non-EUSERC Meter Breaker, Provisions, 200A, 120/240V, Ringless, 12 spaces, 12 circuits, 22 kAIC, Surface mounting, Box size C, Aluminum bus, OH/UG feed, Lever bypass, Five-jaws, 1 socket, #6-350 kcmil line, #6-350 kcmil ground

General specifications

PRODUCT NAME	Eaton residential meter breaker
CATALOG NUMBER	CMBX1212P200BTS
UPC	782116128891
PRODUCT LENGTH/DEPTH	5.38 in
PRODUCT HEIGHT	39.91 in
PRODUCT WIDTH	14.44 in
PRODUCT WEIGHT	34 lb
WARRANTY	Limited lifetime
CERTIFICATIONS	UL Listed

Powering Business Worldwide

Product specifications

TYPE	All-in-ones
INTERRUPT RATING	10 kAIC 22 kAIC
BOX SIZE	C
ENCLOSURE	NEMA 3R
GROUND	#6-350 kcmil
VOLTAGE RATING	120/240 V
NUMBER OF SOCKETS	1
PHASE	Single-phase
USED WITH	Type CH breakers
BYPASS	Lever
NUMBER OF CIRCUITS	12
BUS MATERIAL	Aluminum
FEED TYPE	Top/bottom
MAIN CIRCUIT BREAKER	Provisions
NUMBER OF JAWS	Five-jaw

Resources

CATALOGS	Residential and Light Commercial, Metering Products, Volume 1 Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CMBX1212P200BTS

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.