Product specifications

Eaton C25DRD230A

Catalog Number: C25DRD230A

Eaton definite purpose contactor, Quick, 30A, 110-120 Vac, 50/60 Hz, Open with DIN rail mounting adapter, 15-50A, two- and three-pole, 30A, Contactor,40A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing



General specifications

Product Name
Eaton definite purpose contactor

Catalog Number
C25DRD230A

UPC
782116482993

Product Length/Depth
3.35 in

Product Height
3.75 in

Product Width
2.4 in

Product Weight
1.3 lb

Warranty
1 year

Compliances
RoHS Compliant

Certifications
UL Recognized
CSA Certified

Powering Business Worldwide

Product specifications

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

30 A

Model

Contactor

Connection

Quick

Enclosure

Open with DIN rail mounting adapter

Terminals

Screw/pressure plate and quick connect terminals (side-by-side)

Amperage Rating

30A

Resistive load

40 A

Number Of Poles

Two-pole

Coil

110-120 Vac, 50/60 Hz

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25DRD2 2D PDF

C25DRD2 3D Inventor

C25DRD2 AutoCAD 2D Footprint

C25DRD2 AutoCAD 2D Footprint (mm)

C25DRD2 3D Model Xchange

C25DRD2 2D Drawing Xchange

Specifications and datasheets

Eaton Specification Sheet - C25DRD230A

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia