Product specifications

Eaton V44M31T15EE

Catalog Number: V44M31T15EE

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 440V, Taps: 2 at +2.5% /4 at -2.5%, SV 220Y/127V, 150°C rise w/ 200°C insulation systeam, 15 kVA, EE



Photo is representative

General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
V44M31T15EE

UPC
786680113581

Product Length/Depth
16.5 in

Product Height
30 in

Product Width
23 in

Product Weight
275 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL Listed

Catalog Notes
NEMA TP-1 efficient.

Powering Business Worldwide

Physical Attributes

Coil material
Aluminum

Frame
912D

Tap size
2 at +2.5% FCAN 4 at -2.5% FCBN

Type
Dry type distribution ventilated transformer

Wiring connection
280J

Performance Ratings

Frequency rating
60 Hz

Primary voltage
440 V

Secondary Voltage
220 Y/127 V

Temperature rise
150 °C rise

Volt ampere rating
15 kVA

Miscellaneous

Weathershield
WS38

Resources

Catalogs
Eaton's Volume 2—Commercial Distribution

Specifications and datasheets
Eaton Specification Sheet - V44M31T15EE

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia