
Specifications







Eaton S611A052N3S

S611 Soft Starter, Frame A, 52A, 40 hp, 480V, 26-52 FLA, 130-600V operating, #14-2/0 AWG, 1 conductor, Vertical mounting, 2 Slots, FDC circuit breaker, Class RK5/K5/J Fuse

General specifications	
PRODUCT NAME	Eaton S811+/S801+ soft starter
CATALOG NUMBER	S611A052N3S
UPC	786685480299
PRODUCT LENGTH/DEPTH	7.64 in
PRODUCT HEIGHT	19.45 in
PRODUCT WIDTH	11.58 in
PRODUCT WEIGHT	24 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA file No. 3211-06 IEC 60947-4-2 UL Listed

Powering Business Worldwide

Product specifications

AMPERAGE RATING	52A
HORSEPOWER	40 hp
PHASE	Three-phase
TYPE	Soft starter
USER INTERFACE	LCD
VOLTAGE RATING	480 V
FREQUENCY RATING	47-63 Hz
FUSE SIZE	Class RK5 Class K5 Class J
CIRCUIT BREAKER TYPE	FDC
FRAME SIZE	A
NUMBER OF CONDUCTORS	1
OPERATING TEMPERATURE - MAX	50 °C
FULL LOAD CURRENT RANGE	26-52 FLA
OPERATING VOLTAGE	130-600 V
WIRE SIZE	#14-2/0 AWG
NUMBER OF SLOTS	2
MOUNTING METHOD	Vertical
OPERATING TEMPERATURE - MIN	-20 °C

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1 Product Range Catalog Drives Engineering
MULTIMEDIA	Soft Starter DS7 up to 32 A Soft Starter Product Family Overview Soft starter DS7 up to 200 A
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S611A052N3S
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.