Specifications







Eaton DPF221R

Eaton air conditioning disconnect, Fused pullout, 30A, 120/240V, 10 kAIC, #14-3 Cu/Al 60°C or 75°C, NEMA 3R Galvanized Steel enclosure, 2 hp at 120V, 3 hp at 240V, ANSI 61 gray

General specifications	
PRODUCT NAME	Eaton air conditioning disconnect
CATALOG NUMBER	DPF221R
UPC	782113926865
PRODUCT LENGTH/DEPTH	5.4 in
PRODUCT HEIGHT	8.7 in
PRODUCT WIDTH	3.15 in
PRODUCT WEIGHT	2.7 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed CSA Certified
CATALOG NOTES	For replacement pullout head, order part number 96-3258-4.

Powering Business Worldwide

Product specifications

TYPE	Fused pullout
AMPERAGE RATING	30A
HORSEPOWER	2 hp at 120 V, 3 hp at 240 V
VOLTAGE RATING	120/240 V
WIRE SIZE	#14-3 AWG Cu/Al
COLOR	ANSI 61 gray
ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Galvanized steel
INTERRUPT RATING	10 kAIC

Resources

CATALOGS	Residential and Light Commercial, Air Conditioning Disconnects, Volume 1 Tab 6
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DPF221R

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.