Product specifications

Eaton 14102R6513



Catalog Number: 14102R6513

Eaton Comet 18mm tubular photoelectric sensor, Retroreflective, Right Angle, Output ON, 6.6 ft, 300 mA AC/DC at 20-264 Vac/15-30 Vdc, PVC, AC: L1 switched, DC: NPN open collector, 20-264 Vac 50/60 Hz, 15-30 Vdc (NPN)

General specifications

Product Name
Eaton Comet 18mm tubular photoelectric sensor

Catalog Number
14102R6513

UPC
782113846699

Product Length/Depth
3 in

Product Height
0.71 in

Product Width
0.47 in

Product Weight
0.5 lb

Warranty
3 year

Certifications
UL Recognized
cUL Recognized

Powering Business Worldwide

Product specifications

Contact configuration

AC: L1 switched

DC: NPN open collector

Cord length

79.2 ft

Maximum AC current

300 mA

Maximum DC current

300 mA

Operating temperature - min

-40 °F

Input voltage

20-264 Vac at 50/60 Hz, 15-30 Vdc (NPN)

Cable type

Polyvinyl Chloride (PVC)

LED indicator

Output ON

Enclosure material

Polyurethane foam (RIM)

Type

Photoelectric Sensor

Sensor type

Retroreflective

Contact Rating

300 mA AC/DC at 20-264 Vac/15-30 Vdc

Operating temperature - max

158 °F

Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13, IP69K

Protection

Latching short circuit

Resources

Brochures

Comet series - Photoelectric sensors

Catalogs

Product Range Catalog Sensors – products, basic information, applications

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - 14102R6513



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia