Specifications



Photo is representative





Eaton XTOE100GGS

Eaton C440 electronic overload relay, XT IEC Electronic Overload Relay, 20-100A overload range, 105 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Ground fault w/ selectable class 10, 20 trip type

General specifications	
PRODUCT NAME	Eaton C440 electronic overload relay
CATALOG NUMBER	XTOE100GGS
UPC	786685416588
PRODUCT LENGTH/DEPTH	1.8 in
PRODUCT HEIGHT	4.3 in
PRODUCT WIDTH	1.42 in
PRODUCT WEIGHT	0.87 lb
COMPLIANCES	CE Marked ATEX Compliant RoHS Compliant
CERTIFICATIONS	CSA Certified UL Listed IEC 60947 EN 60947
PRODUCT TYPE	Electronic overload relay

Powering Business Worldwide

Product specifications

OVERLOAD RANGE	20-100A
TYPE	Electronic overload relay
FRAME SIZE	105 mm
MOUNTING METHOD	Direct
CONTACT CONFIGURATION	NO, NC
TRIP TYPE	Ground fault with selectable class 10, 20

Resources

BROCHURES	C440 Electronic Overload Relay
CATALOGS	Motor Control and Protection, NEMA Contactors and Starters, Volume 5, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOE100GGS

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.