Product specifications

Eaton LS-S02-24DFT-ZBZ-X

Catalog Number: LS-S02-24DFT-ZBZ-X

Eaton LS-Titan Safety Interlock Switch, Cabinet Door Interlock, Polyamide PA66-GF25 enclosures, 6A max AC, 3A max DC, 2NC, Slow Make Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Screw Terminals, 24Vdc input



General specifications

Product Name
Eaton LS-Titan Key interlock safety switches

Catalog Number
LS-S02-24DFT-ZBZ-X

UPC
786685393711

Product Length/Depth
2.36 in

Product Height
6.81 in

Product Width
1.21 in

Product Weight
0.95 lb

Warranty
1 year

Compliances
RoHS Compliant

Certifications
UL Listed

Powering Business Worldwide

Product specifications

Enclosure material

Polyamide PA66-GF25

Contact configuration

2 NC, slow make break, positive opening

Type

LS-Titan

Switch type

Cabinet door interlock

Contact Rating

6A at 240Vac, 3A at 24Vdc

Operating temperature - min

-13 °F

Maximum AC current

6 A

Maximum DC current

3 A

Input voltage

24 Vdc

Operating temperature - max

158 °F

Connection

Screw terminal

Environmental rating

IP66, IP67

Resources

Brochures

LS-Titan Safety Limit Switches

Catalogs

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - LS-S02-24DFT-ZBZ-X

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia