Specifications

Eaton XTOB250LC1



Catalog Number: XTOB250LC1

Eaton XT IEC bimetallic overload relay, 200-250A overload range, 140 mm Frame size, 1NO-1NC contact configuration, used with 225-300A, 10A trip type

General specifications

Product Name
Eaton XT IEC bimetallic overload relay

Catalog Number
XTOB250LC1

EAN
4015082100759

Product Length/Depth
5.67 in

Product Height
6.65 in

Product Width
5.04 in

Product Weight
5.5 lb

Compliances
CE Marked
RoHS Compliant
ATEX Compliant

Certifications
UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes
Short-circuit Type 1 rating is 500A and short-circuit Type 2 rating is 400A for separate mounting. The main current parameters are defined by the main current wiring that is used.

Powering Business Worldwide

Product specifications

Overload range

200-250 A

Frame size

140 mm

Resources

Brochures

C440 Electronic Overload Relay

Drawings

XTOB_LC1 2D PDF

XTOB_LC1 3D Model Xchange

XTOB_LC1 3D Inventor

XTOB_LC1 AutoCAD 2D Footprint

XTOB_LC1 2D Drawing Xchange

XTOB_LC1 AutoCAD 2D Footprint (mm)

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Global Data Sheet - XTOB250LC1

Eaton Specification Sheet - XTOB250LC1

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia