Specifications



Photo is representative





Eaton E65-SMPRS9230

Eaton SM Series Rectangular Body Photoelectric Sensor, Sensor distance: 10 Ft., 100 mA max DC, Beam Status PNP, Health PNP Open Collector, 100 mA at 30 Vdc, 4 Pin AMP Connector, 10-30 Vdc input, Polarized Retroreflective, 1.5 Ft. (.5m)

General specifications	
PRODUCT NAME	Eaton E65 SM compact photoelectric sensor
CATALOG NUMBER	E65-SMPRS9230
UPC	782114741832
PRODUCT LENGTH/DEPTH	2.17 in
PRODUCT HEIGHT	1.29 in
PRODUCT WIDTH	1.63 in
PRODUCT WEIGHT	0.1938 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	cUL Listed UL Listed
PRODUCT TYPE	Compact photoelectric sensors

Powering Business Worldwide

Product specifications

CONTACT RATING	200 mA DC NPN / 200 mA AC 3 - Wire
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Lens: polycarbonate Cable jacket: PVC Body: cycoloy
OPERATING MODE	Diffuse reflective
CONNECTION	6.6 ft (2 m) cable
CONTACT CONFIGURATION	AC: L1 switched DC: NPN open collector
SENSOR TYPE	Diffuse reflective
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	18-264 Vac, 18-50 Vdc
LED INDICATOR	Power on: green Marginal gain: orange Output status: red
CORD LENGTH	18 ft
MAXIMUM AC CURRENT	200 mA
MAXIMUM DC CURRENT	200 mA
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP68, IP69K

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - E65-SMPRS9230

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.