Product specifications

Eaton 3BR1224L125S

Catalog Number: 3BR1224L125S

Eaton BR main lug loadcenter,No feed-thru lugs, includes BREQS125 hold-down screw,Main lug,125 A,C1,Aluminum,Cover included,Metallic,10 kAIC,BR,Surface,NEMA 1,24 Circuits,12 Spaces,Four-wire,Three-phase,208 Y/120, 240 V,#6-2/0 AWG Cu/Al



General specifications

Product Name	**Catalog Number**
Eaton BR main lug loadcenter	3BR1224L125S
UPC	**Product Length/Depth**
786676441506	3.88 in
Product Height	**Product Width**
21 in	14.31 in
Product Weight	**Warranty**
19.8 lb	10 year
Certifications	**Catalog Notes**
UL 50 UL 67	Suitable for use as service equipment when no more than 6 main disconnecting means are provided or when not used as lighting & appliance panelboard. Has notch for brhdk125 hold-down kit.

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Special features

No feed-thru lugs, includes BREQS125 hold-down screw

Type

Main lug

Amperage Rating

125 A

Bus material

Aluminum

Cover

Cover included

Main circuit breaker

BR

Mounting

Surface

Number of circuits

24

Number of spaces

12

Phase

Three-phase

Used with

Type BR 1-inch breakers

Voltage rating

208Y/120, 240V

Wire size

#6-2/0 AWG Cu/Al

Box size

C1

Enclosure

NEMA 1

Enclosure material

Metallic

Interrupt rating

10 kAIC

Resources

Brochures

Loadcenters and Circuit Breakers

Type BR 3-Phase Loadcenters

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - BR 1 LOADCENTER, MAIN LUG ONLY, INDOOR NEMA 1, 120/240 VAC, 3 PHASE

Specifications and datasheets

Eaton Specification Sheet - 3BR1224L125S

3-Phase Loadcenter Program

NEMA rating

NEMA 1

Number of wires

4

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia