Specifications







Eaton S611A077N3S

Eaton Soft Starter, Frame A, 77A, 60 hp, 480V, Vertical mounting, 2 Slots, FDC circuit breaker, Class RK5/K5/J Fuse

General specifications

PRODUCT NAME	Eaton S811+/S801+ soft starter
CATALOG NUMBER	S611A077N3S
UPC	786685480312
PRODUCT LENGTH/DEPTH	7.64 in
PRODUCT HEIGHT	15.4 in
PRODUCT WIDTH	11.58 in
PRODUCT WEIGHT	24 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	IEC 60947-4-2 UL Listed CSA file No. 3211-06

Powering Business Worldwide

Product specifications

AMPERAGE RATING	77A
HORSEPOWER	60 hp
PHASE	Three-phase
TYPE	Soft starter
USER INTERFACE	LCD
VOLTAGE RATING	480 V
FUSE SIZE	Class RK5 Class J Class K5
CIRCUIT BREAKER TYPE	FDC
FRAME SIZE	A
OPERATING TEMPERATURE - MAX	50 °C
NUMBER OF SLOTS	2
MOUNTING METHOD	Vertical
OPERATING TEMPERATURE - MIN	-20 °C

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1 Product Range Catalog Drives Engineering
MULTIMEDIA	Soft Starter DS7 up to 32 A Soft starter DS7 up to 200 A Soft Starter Product Family Overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S611A077N3S

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.