# Specifications

## Eaton 7503K15

General Purpose AC Rated Toggle Switches, General purpose, 0.469 in bushing, Circuit position: ON-OFF-ON, 0.563 in lever, 15A at 125V, 10A at 250V, 0.5 hp at 125V, 0.75 hp at 250V, 0.250 in spade terminal, Single-pole, Double-throw

| General specifications | |
|---|---|
| **PRODUCT NAME** | General Purpose AC Rated Toggle Switches |
| **CATALOG NUMBER** | 7503K15 |
| **UPC** | 786685676142 |
| **PRODUCT LENGTH/DEPTH** | 1.312 in |
| **PRODUCT HEIGHT** | 1.2 in |
| **PRODUCT WIDTH** | 0.75 in |
| **WARRANTY** | Eaton Selling Policy 25-000, two (2) years from the date of shipment, excluding incandescent bulbs. LEDs and X Series products are warrantied for one (1) year from the date of shipment. |
| **CERTIFICATIONS** | UL Recognized<br>CSA Certified |
| **GLOBAL CATALOG** | 7503K15 |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **TYPE** | General purpose |
| **AMPERAGE RATING** | 15A at 125V, 10A at 250V |
| **HORSEPOWER** | 0.50 hp at 125 V, 0.75 hp at 250 V |
| **NUMBER OF POLES** | Single-pole |
| **BUSHING LENGTH** | 0.469 in |
| **CIRCUIT POSITION CENTER** | Off |
| **CIRCUIT POSITION DOWN** | On |
| **CIRCUIT POSITION UP** | On |
| **LEVER LENGTH** | 0.563 in |
| **TERMINALS** | 0.250 in spade |
| **THROW TYPE** | Double-throw |

## Resources

| | |
|---|---|
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - 7503K15 |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.