Product specifications

Eaton S20L11S25CU

Catalog Number: S20L11S25CU

Eaton General-Purpose Encapsulated Transformer, EP, Single-phase, PV: 240 x 480V, Taps: 2 at-5% FCBN x 4 at -2.5% FCBN, SV: 120/240V, 115°C, 25 kVA, Copper windings, Frame: 182, 23A, Indoor-Outdoor, 60 Hz, NEMA 3R



Photo is representative

General specifications

Product Name	**Catalog Number**
Eaton General purpose encapsulated transformer	S20L11S25CU
	UPC
	786680104077
Product Length/Depth	**Product Height**
14.12 in	23.31 in
Product Width	**Product Weight**
16.35 in	380 lb
Warranty	**Certifications**
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	CSA Certified UL Listed

Powering Business Worldwide

Physical Attributes

Coil material
Copper

Design
EP

Enclosure
NEMA 3R

Frame
182

Tap size
2 at -5% FCBN x 4 at -2.5% FCBN

Type
General-purpose encapsulated transformer

Wiring connection
23A

Performance Ratings

Frequency rating
60 Hz

Kva Rating
25 kVA

Phase
Single-phase

Primary voltage
240 V, 480 V

Secondary Voltage
120/240 V

Temperature rise
115 °C rise

Volt ampere rating
25 kVA

Miscellaneous

Weathershield
Indoor-Outdoor

Resources

Catalogs
Eaton's Volume 2—Commercial Distribution

Specifications and datasheets
Eaton Specification Sheet - S20L11S25CU

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia