Product specifications

Eaton 3BR1224L125R



Catalog Number: 3BR1224L125R

Eaton BR main lug loadcenter,No feed-thru lugs, includes BREQS125 hold-down screw,Main lug,125 A,C1r,Aluminum,Cover included,NEMA 3R,Metallic,10 kAIC,BR,NEMA 3R,24 Circuits,12 Spaces,Four-wire,Three-phase,208 Y/120, 240 V,#6-2/0 AWG Cu/Al

General specifications

Product Name
Eaton BR main lug loadcenter

Catalog Number
3BR1224L125R

UPC
786676441452

Product Length/Depth
5.19 in

Product Height
21 in

Product Width
14.31 in

Product Weight
24 lb

Warranty
10 year

Certifications
UL 50
UL 67

Catalog Notes
Suitable for use as service equipment when no more than 6 main disconnecting means are provided or when not used as lighting & appliance panelboard. Has notch for brhdk125 hold-down kit.

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Special features

No feed-thru lugs, includes BREQS125 hold-down screw

Type

Main lug

Amperage Rating

125 A

Bus material

Aluminum

Cover

Cover included

Main circuit breaker

BR

Number of circuits

24

Number of spaces

12

Phase

Three-phase

Used with

Type BR 1-inch breakers

Voltage rating

208Y/120, 240V

Wire size

#6-2/0 AWG Cu/Al

Box size

C1R

Enclosure

NEMA 3R

Enclosure material

Metallic

Interrupt rating

10 kAIC

NEMA rating

NEMA 3R

Resources

Brochures

Loadcenters and Circuit Breakers

Type BR 3-Phase Loadcenters

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - BR 1 LOADCENTER, MAIN LUG ONLY, OUTDOOR NEMA 3R, 120/240 VAC, 3 PHASE

Specifications and datasheets

Eaton Specification Sheet - 3BR1224L125R

3-Phase Loadcenter Program

Number of wires

4

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia