Product specifications

Eaton E58-30TD250-GL

Catalog Number: E58-30TD250-GL

Eaton harsh-duty sensor, E58 Harsh Duty, Through Beam, Straight, 30 mm, Light, Power ON, 6.6 ft, 300 mA at 20-132 Vac/15-30 Vdc, PVC, AC: L1 switched, DC: NPN open collector, 20-132 Vac 50/60 Hz, 15-30 Vdc



General specifications

Product Name
Eaton harsh-duty sensor

Catalog Number
E58-30TD250-GL

UPC
782114091531

Product Length/Depth
4.36 in

Product Height
1.18 in

Product Width
1.18 in

Product Weight
0.45 lb

Warranty
3 year

Certifications
UL Listed

Powering Business Worldwide

Product specifications

Contact configuration

AC: L1 switched

DC: NPN open collector

Cord length

79.2 ft

Maximum AC current

300 mA

Maximum DC current

300 mA

Operating temperature - min

-40 °F

Input voltage

20-132 Vac at 50/60 Hz, 15-30 Vdc

Cable type

Polyvinyl Chloride (PVC)

LED indicator

Power on

Enclosure material

303 stainless steel

Series

E58 harsh duty

Type

Photoelectric Sensor

Operating mode

Light

Sensor type

Through beam

Contact Rating

300 mA at 20-132 Vac/15-30 Vdc

Operating temperature - max

131 °F

Environmental rating

NEMA 1, NEMA 2, NEMA 3, NEMA 3R, NEMA 3S, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 12K, NEMA 13, IP69K

Resources

Brochures

Test the Best Photoelectric Sensors: E58 Series Harsh Duty

Catalogs

Product Range Catalog Sensors – products, basic information, applications

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - E58-30TD250-GL

Protection

Latching short circuit

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia