Specifications

Eaton TMRP5100

TMRP Series Timing Relay, Octal style terminals, 11 pins, Control switch trigger, 0.1 seconds-9,990 hours time delay, 12-240 Vac/dc input voltage, ON/OFF delay, 90% silver, 10% nickel, 12A contact rating, DPDT contact configuration,

General specifications	
PRODUCT NAME	Eaton timing relay
CATALOG NUMBER	TMRP5100
UPC	786685215358
PRODUCT LENGTH/DEPTH	3.46 in
PRODUCT HEIGHT	1.88 in
PRODUCT WIDTH	1.88 in
PRODUCT WEIGHT	0.2 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Timing relay

Powering Business Worldwide

Product specifications

TYPE	Timing relay
CONTACT RATING	12A
NUMBER OF PINS	11
CONTACT MATERIAL	10% nickel 90% silver
OPERATING MODE	Control switch trigger
CONTACT CONFIGURATION	DPDT
SERIES	TMRP
OPTIONS	Plastic dust cover
FUNCTIONS	Single pulse generator Single shot leading edge voltage controlled and control input ON/OFF delay Memory latch Power triggered Flasher-pause or ON first Retriggerable single shot
INPUT VOLTAGE	12-240 Vac/dc
TERMINALS	Octal
TIME DELAY	0.1 seconds-9990 hours

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - TMRP5100

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.