Product specifications

Eaton C25DRF240B

Catalog Number: C25DRF240B

Eaton definite purpose contactor, Quick, 40A, 208-240 Vac, 50/60 Hz, Open with DIN rail mounting adapter,15-50A, two- and three-pole, 40A, Contactor,50A, Box lugs (posidrive setscrew) and quick connect terminals (side-by-side),Non-reversing



General specifications

Product Name
Eaton definite purpose contactor

Catalog Number
C25DRF240B

UPC
782116483167

Product Length/Depth
3.35 in

Product Height
3.75 in

Product Width
2.4 in

Product Weight
1.3 lb

Warranty
1 year

Compliances
RoHS Compliant

Certifications
CSA Certified
UL Recognized

Powering Business Worldwide

Product specifications

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

40 A

Model

Contactor

Connection

Quick

Enclosure

Open with DIN rail mounting adapter

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

Amperage Rating

40A

Resistive load

50 A

Number Of Poles

Two-pole

Coil

208-240 Vac, 50/60 Hz

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25DRF2 AutoCAD 2D Footprint (mm)

C25DRF2 3D Model Xchange

C25DRF2 2D PDF

C25DRF2 2D Drawing Xchange

C25DRF2 3D Inventor

C25DRF2 AutoCAD 2D Footprint

Specifications and datasheets

Eaton Specification Sheet - C25DRF240B

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia