Product specifications

Eaton BRP24L125G

Catalog Number: BRP24L125G

Eaton Eaton BR main lug loadcenter, Ground bar, Main lug only, 125 A, X3, Aluminum, NEMA 1, Metallic, 10kAIC, BR2125, Surface, flush, 48 Circuits, Twenty-four pole, 24 Spaces, Two hots, a neutral, and a ground, Single-phase, 120/240V



Photo is representative

General specifications

Product Name
Eaton BR main lug loadcenter

Catalog Number
BRP24L125G

UPC
786689053369

Product Length/Depth
23 in

Product Height
3.88 in

Product Width
14.31 in

Product Weight
20 lb

Warranty
10 year

Certifications
UL 50
UL 67

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

MLO

Amperage Rating

125 A

Bus material

Aluminum

Cover

Cover included

Main circuit breaker

BR2125

Mounting

Surface, flush

Number of circuits

48

Number Of Poles

Single-pole

Number of spaces

24

Phase

Single-phase

Used with

Type BR 1-inch breakers

Voltage rating

120/240V

Wire size

#6-1/0 AWG Cu/Al

Box size

X3

Enclosure

NEMA 1

Enclosure material

Metallic

Interrupt rating

10 kAIC

Resources

Brochures

Loadcenters and Circuit Breakers

Specifications and datasheets

Eaton Specification Sheet - BRP24L125G

NEMA rating

NEMA 1

Number of wires

Two hots, neutral and ground

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia