Specifications



Photo is representative





Eaton DG225FRK

Eaton General duty cartridge fuse safety switch, 400 A, NEMA 3R, Painted galvanized steel, Class H fuses, Fusible without neutral, Two-pole, Two-wire, Category: general duty safety switch, 240 V

General specifications

PRODUCT NAME	Eaton general duty cartridge fuse safety switch
CATALOG NUMBER	DG225FRK
UPC	782114001950
PRODUCT LENGTH/DEPTH	7.27 in
PRODUCT HEIGHT	44.74 in
PRODUCT WIDTH	23.08 in
PRODUCT WEIGHT	120 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEC 230.62 (C) Compliant Barrier
CERTIFICATIONS	UL Listed
CATALOG NOTES	Maximum hp ratings apply only when dual element fuses are used. Solid neutral bars are not included. Must be ordered separately.
PRODUCT TYPE	Cartridge fuse safety switch

Powering Business Worldwide

Physical Attributes

ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Fusible without neutral
NUMBER OF POLES	Two-pole
NUMBER OF WIRES	2
TYPE	General duty, cartridge fused

Performance Ratings

AMPERAGE RATING	400A
FUSE CLASS PROVISION	Class H fuses
VOLTAGE RATING	240V

Miscellaneous

PRODUCT CATEGORY	General duty safety switch

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
MULTIMEDIA	Double Up on Safety Switching Devices Flex Center
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DG225FRK

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.