Specifications

Eaton XTRM10A40B

Catalog Number: XTRM10A40B

XT IEC Miniature Control Relay, Screw terminals, 45 mm - mini Frame size, 4NO contact configuration, 220V 50 Hz, 240V 60 Hz coil, 10A conventional thermal rating, 6A at 220/230/240V; 3A at 380/400/415V rated operational voltage



General specifications

Product Name	**Catalog Number**
Eaton XT IEC control relay	XTRM10A40B
EAN	**Product Length/Depth**
4015080517580	2 in
Product Height	**Product Width**
2.5 in	2.5 in
Product Weight	**Certifications**
0.3 lb	UL Listed

Powering Business Worldwide

Product specifications

Conventional thermal current

10A

Type

Control relay

Frame size

45 mm - mini

Coil

220-240 Vac, 50/60 Hz

Coil voltage

220-240 Vac, 50/60 Hz

Contact configuration

4 NO

Terminals

Screw terminals

Rated operational current

3 A at 380/400/415 V

6 A at 220/230/240 V

Resources

Drawings

XTRM 3D Model Xchange

XTRM 2D PDF

XTRM 2D Drawing Xchange

XTRM AutoCAD 2D Footprint

XTRM 3D Inventor

Specifications and datasheets

Eaton Specification Sheet - XTRM10A40B

Global Data Sheet - XTRM10A40B

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia