Product specifications

Eaton C22M125

Catalog Number: C22M125

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 125 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CH22 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C22M125

UPC
051712589949

EAN
5027590495677

Product Length/Depth
58 mm

Product Height
22.2 mm

Product Width
22.2 mm

Product Weight
55.9 g

Warranty
1 year limited

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

fuse

Application

motor protection
for industrial applications

Amperage Rating

125 A

Fuse size

22 x 58 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

400 V

Class

Class aM

Fuse type

C22M

Utilization category

aM (switchgear protection)

Fuse indicator

Other

Watt losses

8.42 W

Connection

Ferrule end x ferrule end

Construction size

22 mm x 58 mm

Fuse shape

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Cylindrical

Voltage type

AC

Suitable for

CH22 Modular fuse holder

Material

Ceramic

Mounting method

22 x 58 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

400 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia