Specifications

Eaton DH221NWK

Eaton Heavy duty single-throw fused safety switch, Corrosion resistant, 30 A, NEMA 4X, Grade 304 stainless steel, neutral, Two-pole, Three-wire, 240 V, Max Hp: 1.5, 3 hp/3, 7.5 hp/5 hp (1,3PH @ Std fuse/time delay/250 Vdc), #14-#2 Cu/Al

General specifications	
PRODUCT NAME	Eaton heavy duty fusible safety switch
CATALOG NUMBER	DH221NWK
UPC	782113205403
PRODUCT LENGTH/DEPTH	20 in
PRODUCT HEIGHT	8.5 in
PRODUCT WIDTH	9.5 in
PRODUCT WEIGHT	21 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed
CATALOG NOTES	3-Phase hp ratings shown are grounded B phase ratings; UL listed
PRODUCT TYPE	Fusible safety switch

Powering Business Worldwide

Physical Attributes

ENCLOSURE	NEMA 4X
ENCLOSURE MATERIAL	304 stainless steel
FUSE CLASS PROVISION	Class H
FUSE CONFIGURATION	Fusible with neutral
NUMBER OF POLES	Two-pole
NUMBER OF WIRES	3
TYPE	Heavy duty fusible safety switch

Performance Ratings

AMPERAGE RATING	30A
HP RATING - MAX	1.5, 3 hp/3, 7.5 hp/5 hp (1,3PH @ Std fuse/time delay/250 Vdc)
NEMA RATING	NEMA 4X (Stainless)
VOLTAGE RATING	240V

Miscellaneous

PRODUCT CATEGORY	Heavy Duty, Fusible with neutral

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DH221NWK

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.