Product specifications

Eaton V48M28T7716CU

Catalog Number: V48M28T7716CU

Eaton General purpose ventilated transformer, Fungus proof, CU windings, DOE 2016, NEMA 2, 750 kVA, Floor mnt, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 750 kVA, Not Required



General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
V48M28T7716CU

UPC
786680221521

Product Length/Depth
41.5 in

Product Height
64 in

Product Width
49 in

Product Weight
4250 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
DOE2016 Efficient

Certifications
UL Listed

Catalog Notes
10 CFR Part 431 (2016) Efficient

Powering Business Worldwide

Physical Attributes

Coil material

Copper

Enclosure

NEMA 2

Insulation

220 °C

Mounting

Floor

Tap size

2 at +2.5%, 4 at -2.5%

Type

Energy-efficient ventilated dry-type transformer

Performance Ratings

Efficiency

10 CFR Part 431-2016 (DOE 2016)

Frequency rating

60 Hz

Kva Rating

750 kVA

Primary voltage

480 V delta

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

150 °C rise

Volt ampere rating

750 kVA

Voltage rating

480 Vac-208Y/120 Vac

Miscellaneous

Weathershield

Not required

Resources

Brochures

Eaton's high-efficiency dry-type transformers

Eaton's low-voltage dry-type distribution transformers

Specifications and datasheets

Eaton Specification Sheet - V48M28T7716CU



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia