Product specifications

Eaton FWC-4A10F

Catalog Number: FWC-4A10F

Eaton Bussmann series FWC high speed cylindrical fuse, 500V, 4A, Non Indicating, High speed fuse, Cylindrical

General specifications

Product Name
Eaton Bussmann series high speed cylindrical fuse

Catalog Number
FWC-4A10F

UPC
051712246071

EAN
5027590499408

Product Length/Depth
44 mm

Product Height
23 mm

Product Width
54 mm

Product Weight
8.8 g

Warranty
Not Applicable

Compliances
RoHS Compliant

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

4 A

Accessories

BMM Fuse block

CHM modular fuse holder

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

10 x 38 mm

Class

Class aR

Clearing (I2T)

32

Watt losses

1.5 W

Construction type

Ceramic tube

Fuse shape

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Installation videos

Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications (brightcove.net)

Technical data sheets

720011 FWC

Cylindrical

Pre arc (I2T)

5.2

Interrupt rating

200 kAIC

Construction size

10 x 38 mm

10 mm x 38 mm

Material

Ceramic

Mounting method

Cylindrical

Packaging type

Standard

Quantity

10

Voltage rating

600 V

Fuse type

FWC-A10F

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia