Specifications

Eaton 7505K6

General Purpose AC Rated Toggle Switches, General purpose, 0.469 in bushing, Circuit position: ON-NONE-ON, 0.563 in lever, 15A at 125V, 10A at 250V, 0.5 hp at 125V, 0.75 hp at 250V, 0.250 in spade terminal, Single-pole, Double-throw

General specifications	
PRODUCT NAME	General Purpose AC Rated Toggle Switches
CATALOG NUMBER	7505K6
UPC	786685676166
PRODUCT LENGTH/DEPTH	1.312 in
PRODUCT HEIGHT	1.2 in
PRODUCT WIDTH	0.75 in
WARRANTY	Eaton Selling Policy 25-000, two (2) years from the date of shipment, excluding incandescent bulbs. LEDs and X Series products are warrantied for one (1) year from the date of shipment.
CERTIFICATIONS	UL Recognized CSA Certified
GLOBAL CATALOG	7505K6

Powering Business Worldwide

Product specifications

TYPE	General purpose
AMPERAGE RATING	15A at 125V, 10A at 250V
HORSEPOWER	0.50 hp at 125 V, 0.75 hp at 250 V
NUMBER OF POLES	Single-pole
BUSHING LENGTH	0.469 in
CIRCUIT POSITION CENTER	None
CIRCUIT POSITION DOWN	On
CIRCUIT POSITION UP	On
LEVER LENGTH	0.563 in
TERMINALS	0.250 in spade
THROW TYPE	Double-throw

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 7505K6

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.