Product specifications

Eaton DG1-357D5FB-C54C



Catalog Number: DG1-357D5FB-C54C

Eaton PowerXL DG1 variable frequency drive, 208-240V input 3.7 kW 5 Hp CT 3PH 50/60 Hz 7.5A output IP54/type 12 FR2 LCD Internal EMC filter and DC choke EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU ports 2 exp slots Brake chopper

General specifications

Product Name
Eaton PowerXL DG1 variable frequency drive

Catalog Number
DG1-357D5FB-C54C

UPC
786685975542

Product Length/Depth
17 in

Product Height
12 in

Product Width
9.5 in

Product Weight
18 lb

Warranty
Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.

Compliances
CE Marked
C-Tick Compliant
RoHS Compliant
GoST-R

Certifications
cUL Listed
UL Listed
UL 508C
EN ISO 13849-1
EN 62061
IEC 61508

Powering Business Worldwide

Product specifications

Max overload

110% for 1 minute

Protection filtering

Internal EMC filter and DC choke

High overload (CT) amps

7.5 A

Phase

Three-phase in, three-phase out

Motor control modes

Frequency, Speed, Open-loop speed, Open-loop torque

Internal DC choke

Yes

Conformal coated boards

Yes

Low overload (VT) kW

5.5 kW

Enclosure

IP54/type 12

Number of slots

2 expansion slots

Communications onboard

EtherNet/IP, Modbus TCP, RS-485: Modbus RTU, BACnet MS/TP

Motor type

Inductio, PM (IPM & SPM)

Electromagnetic compatibility filter

EMC Filter

User interface

Graphical Keypad

Brake chopper

Brake chopper

Power consumption

3.7 kW

High overload (CT) kW

3.7 kW

Resources

Application notes

Load balancing in multi motor applications

Digital I/Os

Dual Rating What exactly does that mean?

Starting, stopping and operation

Real time clock and use of the timers

Electromagnetic compatibility (EMC)

Torque control

Smoke Mode and fire mode

PID controller

Connecting drives to generator supplies

DG1 in pump and fan applications

Motor data and V/f curves

Operating at low temperatures

Analog I/Os

Catalogs

Product Range Catalog Drives Engineering

Product Datasheet - DG1-357D5FB-C54C

Specifications and datasheets

Eaton Specification Sheet - DG1-357D5FB-C54C

Horsepower

5 hp

Frequency rating

50-60 Hz

Protection

Internal EMC filter, DC choke

Communication

EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU communication

Special features

Coated boards

Input voltage

230 V, 208-240 V(-15%, +10%)

Material

Coated board

Low overload (VT) hp

7.5 hp

Output current - max

7.5 A

Low overload (VT) amps

10 A

High overload (CT) hp

5 hp

Frame size

2

Output frequency range

0 - 400 Hz

Input voltage range

525 - 600 V

Recommended fuse size

16

Keypad

Included

Input frequency range

50 - 60 Hz

Software

Active energy control, quick start wizard

Torque rating

CT

Display

LCD graphical

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia