Specifications



Photo is representative

Eaton MV155F1DCX100E

Eaton Bussmann series MV055 E-Rated medium voltage fuse, 15.5 kV, 100A, 50 kAIC, Non Indicating, Current limiting, Ferrule end X ferrule end, Class E, Fiberglass tube, 1 - MV155F1DCX100E

General specifications

PRODUCT NAME	Eaton Bussmann series MV155F E-rated fuse
CATALOG NUMBER	MV155F1DCX100E
UPC	051712269391
PRODUCT LENGTH/DEPTH	0.75 in
PRODUCT HEIGHT	23 in
PRODUCT WIDTH	0.75 in
PRODUCT WEIGHT	12.15 lb
WARRANTY	Not Applicable
COMPLIANCES	Contact factory
CERTIFICATIONS	ANSI
PRODUCT TYPE	Fuse

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	100 A
INTERRUPT RATING	50 kAIC
VOLTAGE RATING	15.5 kV

Physical details

MATERIAL	Fiberglass tube
PACKAGING TYPE	Standard

General information

BARRELS	1
CLASS	Class E
CONNECTION	Ferrule end x ferrule end
ELEMENT	Silver ribbon
FUSE INDICATOR	Non Indicating

Resources

CATALOGS	Bussmann series 2018 full line catalog no. 1007, section 7 - medium voltage fuses Bussmann series complete full line catalog no. 1007 MV155F1DCX100E~MEDIUM VOLTAGE E-RATED
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - MV155F1DCX100E

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.