Product specifications

Eaton 14150ALS2350

Catalog Number: 14150ALS2350

Eaton OEM Prism 18mm tubular photoelectric sensor, Retroreflective, Forward Viewing, Output ON, 6.6 ft, 80 mA AC/100 mA DC at 20-132V, PVC, Isolated SSR, 20-132 Vac 50/60 Hz, 15-30 Vdc, Plastic mounting nut



General specifications

Product Name
Eaton OEM Prism 18mm tubular photoelectric sensor

Catalog Number
14150ALS2350

UPC
786685879338

Product Length/Depth
2.75 in

Product Height
0.71 in

Product Width
0.47 in

Product Weight
0.2 lb

Warranty
3 year

Certifications
UL Listed
cUL Listed
CE

Powering Business Worldwide

Product specifications

Contact configuration

Isolated solid state relay

Cord length

79.2 ft

Maximum AC current

80 mA

Maximum DC current

100 mA

Operating temperature - min

-13 °F

Input voltage

20-132 Vac at 50/60 Hz, 15-30 Vdc

Cable type

Polyvinyl Chloride (PVC)

LED indicator

Output ON

Enclosure material

Polyurethane foam (RIM)

Accessories

Plastic mounting nut

Type

Photoelectric Sensor

Sensor type

Retroreflective

Contact Rating

80 mA AC/100 mA DC at 20-132V

Operating temperature - max

131 °F

Environmental rating

NEMA 1, NEMA 2, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13

Protection

Protected for loads < 32 Vac or 2 Vdc

Resources

Specifications and datasheets

Eaton Specification Sheet - 14150ALS2350



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia