Product specifications

Eaton LS-S11-24DMT-ZBZ-X

Catalog Number: LS-S11-24DMT-ZBZ-X

Eaton LS-Titan Safety Interlock Switch, Cabinet Door Interlock, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 1NO-1NC, Slow Make Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Screw Terminals, 24Vdc input



General specifications

Product Name	**Catalog Number**
Eaton LS-Titan miniature DIN limit switch	LS-S11-24DMT-ZBZ-X
UPC	**Product Length/Depth**
786685393698	2.36 in
Product Height	**Product Width**
6.81 in	1.21 in
Product Weight	**Warranty**
0.95 lb	1 year
Compliances	**Certifications**
RoHS Compliant	UL Listed

Powering Business Worldwide

Product specifications

Enclosure material

Polyamide PA66-GF25

Contact configuration

1 NO-1 NC, slow make break, positive opening

Type

LS-Titan

Switch type

Cabinet door interlock

Contact Rating

6A at 240Vac, 3A at 24Vdc

Operating temperature - min

-13 °F

Maximum AC current

6 A

Maximum DC current

3 A

Input voltage

24 Vdc

Operating temperature - max

158 °F

Connection

Screw terminal

Environmental rating

IP66, IP67

Resources

Brochures

LS-Titan Safety Limit Switches

Catalogs

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - LS-S11-24DMT-ZBZ-X

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia