Specifications



Photo is representative





Eaton C25DRD330A

Eaton definite purpose contactor, DIN rail mounting adapter, Quick, 40A, Quick connect , 24 Vac, 50/60 Hz, Open with DIN rail mounting adapter, 15-50A, 2P and 3P, 40A, Contactor, 3P, Global listed, D1, Box lugs (posidrive setscrew),

General specifications	
PRODUCT NAME	Eaton definite purpose contactor
CATALOG NUMBER	C25DRD330A
UPC	782116483792
PRODUCT LENGTH/DEPTH	3.35 in
PRODUCT HEIGHT	3.75 in
PRODUCT WIDTH	2.4 in
PRODUCT WEIGHT	1.19 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	CSA Certified UL Recognized UL Listed file E1491 (Guide Number NLDX2)

Powering Business Worldwide

Product specifications

AMPERAGE RATING	30A
NUMBER OF POLES	Three-pole
OPTIONS	Global listed
TYPE	Non-reversing
AUXILIARY CONTACTS	Pressure plate quick connect (side-by-side)
COIL	110-120 Vac, 50/60 Hz
COIL VOLTAGE	24 Vac, 50/60 Hz
ENCLOSURE	Open with DIN rail mounting adapter
FRAME SIZE	15-50 A, two-pole and three-pole
INDUCTIVE FULL LOAD	30 A
MODEL	Contactor
RESISTIVE LOAD	40 A
SERIES	D1
TERMINALS	Screw
CONNECTION	Quick

Resources

CATALOGS	Motor Control and Protection, Definite Purpose Contactors and Starters, Volume 5, Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - C25DRD330A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.