Specifications



Photo is representative





Eaton DS7-342SX024N0-N

Eaton DS7 soft start controller, 22 second ramp, one start per hour, 300% current limit at 40°C, 22 A, 5 hp at 200 V, 7.5 hp at 230 V, 15 hp at 480 V, HFD3060 max breaker, 40 A Class RK5 max fuse

General specifications

PRODUCT NAME	Eaton DS7 soft start controller
CATALOG NUMBER	DS7-342SX024N0-N
UPC	786685457697
PRODUCT LENGTH/DEPTH	7 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	5.5 in
PRODUCT WEIGHT	1.3 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	Contact Manufacturer
PRODUCT TYPE	Soft start controller

Powering Business Worldwide

Product specifications

AMPERAGE RATING	22A
TYPE	22 second ramp, one start per hour, 300% current limit at 40°C
FUSE SIZE	40 A class RK5 max
CIRCUIT BREAKER TYPE	HFD3060
RATING	5 hp at 200 V, 7.5 hp at 230 V, 15 hp at 480 V

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1
MULTIMEDIA	Soft starter DS7 up to 200 A Soft Starter DS7 up to 32 A Soft Starter Product Family Overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DS7-342SX024N0-N

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.