Product specifications

Eaton SP6483D

Catalog Number: SP6483D

Eaton Crouse-Hinds series SP plug, 60A, 0.500-0.875" cable diameter, Three-wire, four-pole, Brass contacts, 60-400 Hz, Style 2, Copper-free aluminum, With cable grip and neoprene bushing, 480 Vac, Used with SRD threaded cap receptacles

General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series SP plug	SP6483D
UPC	**Product Weight**
782274083117	5.39 lb

Powering Business Worldwide

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class II, Division 1
Class I, Division 2
Class I, Division 1
Class II, Division 2
Class III

NEMA Rating

7
3
9
12

Product specifications

Amperage Rating

60A

Configuration

Three-wire, four-pole

Cable diameter

0.500-0.875 in

Grounding style

Style 2

Voltage rating

480 Vac

Frequency rating

60-400 Hz

Material

Copper-free aluminum

Contact material

Brass

Special features

With cable grip and neoprene bushing

Type

Used with SRD threaded cap receptacles

Resources

Catalogs

BHR and SRD Explosionproof Interlock Receptacles catalog page

Certification reports

BHR and SRD Explosionproof Interlock Receptacles UL certification

BHR and SRD Explosionproof Interlock Receptacles Canadian certification

Installation instructions

IF 308 - SRD Interlock Receptacles

Specifications and datasheets

Eaton Specification Sheet - SP6483D



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia