Product specifications

Eaton TMCX250 2

Catalog Number: TMCX250 2

Eaton Crouse-Hinds series Terminator II TMCX cable gland,TSC compound,Cable Range:2.24-3.28",Cable Sealing:2 (M),Metal-cladcorrugated armoured,TECK armoured,armoured barrier and tray cable,Armoured gland, Aluminum, 2-1/2" NPT

General specifications

Product Name Eaton Crouse-Hinds series Terminator II TMCX cable gland	**Catalog Number** TMCX250 2
	UPC 662276438750
Product Length/Depth 7.61 in	**Product Height** 5.61 in
Product Width 5.61 in	**Product Weight** 14.82 lb

Powering Business Worldwide

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class II, Division 1

Class III

NEMA Rating

4X

Product specifications

Protection type

Explosion-proof

Cable type

Armoured barrier

Metal-clad with interlocked or continuously welded corrugated armoured

TECK armoured

Tray cable

Gland type

Armoured

Thread Size

2-1/2"

Thread type

NPT

Cable sealing range

2 (M)

Cable range (min/max)

2.24-3.28"

Material

Aluminum

Barrier type

TSC Compound

Resources

3D CAD drawing package

Eaton Crouse-Hinds TMCX250 2 3D drawing

Brochures

Crouse-Hinds series Chico LiquidSeal flyer

Crouse-Hinds series TMCX II brochure

Catalogs

Crouse-Hinds series TMCX II catalog page

Certification reports

TMCX II Explosionproof Armoured Barrier and Non-armoured Barrier Gland UL certification

TMCX II Explosionproof Armoured Barrier and Non-armoured Barrier

Gland Canadian certification

Installation instructions

IF 1647 - TMCX Terminator II Cable Gland

IF 1647B - TMCX Terminator II Cable Gland

Specifications and datasheets

Eaton Specification Sheet - TMCX250 2

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia