Specifications



Photo is representative





Eaton 5MCLS-24R-B

Eaton Bussmann series 5MCLS fuse, 24R designation, 4.8 kV, 450A, MCLS, MCLS, Class R, Single barrel - 5MCLS-24R-B

General specifications	
PRODUCT NAME	Eaton Bussmann series MCLS fuse
CATALOG NUMBER	5MCLS-24R-B
UPC	786685409375
PRODUCT LENGTH/DEPTH	0.001 in
PRODUCT HEIGHT	0.001 in
PRODUCT WIDTH	0.001 in
PRODUCT WEIGHT	0.001 lb
WARRANTY	Not Applicable
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	IEEE Std. C37.41 Not Applicable
CATALOG NOTES	Consult factory for mountings.

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	450 A
INTERRUPT RATING	50 kAIC
VOLTAGE RATING	4.8 kV

General information

BARRELS	2
CLASS	Class R
SPECIAL FEATURES	24R designation

Resources

BROCHURES	5MCLS-24R-B~5984C57G24~24R MOTOR STARTER FUSE FOR
CATALOGS	Current Limiting Fuses, Volume 14, Tab 3 Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 5MCLS-24R-B

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.