Product specifications

Eaton BR2424L125G

Catalog Number: BR2424L125G

Eaton Eaton BR main lug loadcenter,Ground bar,includes BREQS125 hold-down screw, 125 A,C2,Aluminum, NEMA 1,Metallic,10 kAIC,Combination,NEMA 1,24 Circuits,Twenty-four pole,24 Spaces,Three-wire,Single-phase,120/240V,#6-2/0 AWG Cu/Al



General specifications

Product Name	**Catalog Number**
Eaton BR main lug loadcenter	BR2424L125G
UPC	**Product Length/Depth**
786676001199	3.88 in
Product Height	**Product Width**
23 in	14.31 in
Product Weight	**Warranty**
16 lb	10 year
Certifications	**Catalog Notes**
UL 50 UL 67	Ground bar gbk1220 is installed. Has notch for brhdk125 hold-down kit.

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Special features

Ground bar, includes BREQS125 hold-down screw

Type

Main lug

Amperage Rating

125 A

Bus material

Aluminum

Cover

Cover included

Mounting

Combination

Number of circuits

24

Number of spaces

24

Phase

Single-phase

Used with

Type BR 1-inch breakers

Voltage rating

120/240V

Wire size

#6-2/0 AWG Cu/Al

Box size

C2

Enclosure

NEMA 1

Enclosure material

Metallic

Interrupt rating

10 kAIC

Number of wires

3

Resources

Brochures

Loadcenters and Circuit Breakers

Type BR Arc Fault Circuit Breakers and Loadcenters

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - BR 1 LOADCENTER, MAIN LUG ONLY, INDOOR NEMA 1, 120/240 VAC, 1 PHASE

Installation instructions

Cutler-Hammer Type CH and BR Loadcenters - Instructions

Specifications and datasheets

Eaton Specification Sheet - BR2424L125G



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia